

GG E10.40 RRQ FG

ArticleNo. 54660

FBGG054660

General information

Product group	High Performance Flat Belts
Product sub type	QuickSplice
Industry segment(s)	Container & Packaging
Application(s)	Boxfolding
Main product feature(s)	High grip, Energy saving, Foodgrade
Indication(s) of use	High efficient XNBR cover

Belt construction

Top side	material	XNBR elastomer
	finish	Rough
	color	Grey
Tension member		Polyester fabric
Bottom side / Pulley side	material	XNBR elastomer
	finish	Rough
	color	Grey

Characteristics

Food Grade	YES	According: FDA; EC 1935/2004, EU 10/2011
Antistatic (AS)	YES	According EN ISO 284
High conductive (HC)	NO	
ATEX	NO	

Technical belt data

Belt thickness	DIN EN ISO 2286-3	4.0 mm
Belt thickness tolerance	+/-	0.2 mm
Weight	DIN EN ISO 290703-1	4.5 kg/m ²
Force at 1 % elongation static	DIN EN ISO 21181	17.0 N/mm
Force at 1 % elongation dynamic	DIN EN ISO 21181	10.0 N/mm
Recommended elongation	from/to	0.4 / 0.6 %
Coefficient of friction, bottom (pulley) side to steel, dynamic	DIN EN ISO 21182	0.6 μ
Coefficient of friction, top side to steel, dynamic	DIN EN ISO 21182	0.6 μ
Min. pulley diameter	flexing	40 mm
	back flexing	40 mm
Temperature range	from/to	+0 / +60 °C
Standard sales width		290/570 mm

Endless method

Recommended splice method	QuickSplice110
Alternative splice method	QuickSplice50

Additional information

The information applies at approx. 20°C/68°F and 65% relative humidity.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc® technical calculation program.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.