

## GG S11.26 RFC

ArticleNo. 54530

FBGG054530

### General information

<b>Product group</b>	High Performance Flat Belts
<b>Product sub type</b>	Classic
<b>Industry segment(s)</b>	Textile, Logistics
<b>Application(s)</b>	Yarn spinning, Twisting
<b>Main product feature(s)</b>	Shock absorbing, Abrasion resistant
<b>Indication(s) of use</b>	High efficient rubber cover, Note: not suitable for speed higher than 100'000RPM

### Belt construction

<b>Top side</b>	<b>material</b>	XNBR elastomer
	<b>finish</b>	Fine
	<b>color</b>	Blue
<b>Tension member</b>		Polyamide foil
<b>Bottom side / Pulley side</b>	<b>material</b>	XNBR elastomer
	<b>finish</b>	Rough
	<b>color</b>	Grey

### Characteristics

<b>Food Grade</b>	NO
<b>Antistatic (AS)</b>	YES According EN ISO 284
<b>High conductive (HC)</b>	NO
<b>ATEX</b>	NO

### Technical belt data

<b>Belt thickness</b>	DIN EN ISO 2286-3	2.6 mm
<b>Belt thickness tolerance</b>	+/-	0.2 mm
<b>Weight</b>	DIN EN ISO 290703-1	3.0 kg/m <sup>2</sup>
<b>Force at 2 % elongation static</b>	DIN EN ISO 21181	>36.5 N/mm
<b>Force at 1 % elongation dynamic</b>	DIN EN ISO 21181	11.0 N/mm
<b>Recommended elongation</b>	from/to	2.0 / 3.0 %
<b>Coefficient of friction, bottom (pulley) side to steel, dynamic</b>	DIN EN ISO 21182	0.6 μ
<b>Coefficient of friction, top side to steel, dynamic</b>	DIN EN ISO 21182	0.6 μ
<b>Min. pulley diameter</b>	flexing	60 mm
	back flexing	60 mm
<b>Temperature range</b>	from/to	+0 / +80 °C
<b>Standard sales width</b>		290/570 mm

### Endless method

<b>Recommended splice method</b>	WedgeSkive75D-1.5-2.8
<b>Alternative splice method</b>	-

### Additional information

The information applies at approx. 20°C/68°F and 65% relative humidity.

Consult our specialists for further instructions regarding joining, storage & maintenance, tracking & tensioning.

Consult our specialists for calculations with our E-RappCalc® technical calculation program.

Because of continuous development, the presented data is subject to alteration. This data replaces that included in previous publications. Ammeraal Beltech excludes any liability for the incorrect use of the above stated information. Subject to the general terms and conditions of sale and delivery, as applied by its operating companies, are all activities performed and services rendered by Ammeraal Beltech.